



Terminal box KG



Terminal boxes are available with screw-mounted cover, covers secured by latches or covers with latches and hinges.

Standard equipment

- Sheet metal thickness: Cabinet body 1.5 mm / door 2.0 mm
- Material: Made entirely from stainless steel
Material 1.4301 (AISI 304)
- Surface: Polished (grain size 400)
- Locking mechanism: Cover locked with screws
- Seal: Silicone profile gasket, 25 x 10, blue
- Protection class: IP 65
- Cover with earth bolts

Equipment options

- | | | | |
|------------------------|----------------------------------|---------------------------|-----------|
| Stainless steel: | ■ 1.4571 (AISI 316) | ■ 1.4404 (AISI 316L) | |
| Surface: | ■ Grain-blasted | ■ Grain size 240 polished | ■ Pickled |
| Hinges: | ■ 117° inside hinges | | |
| Latch lock mechanisms: | ■ Double bit 3 mm | | |
| | ■ Double bit 5 mm | | |
| | ■ Triangle 8 mm | | |
| | ■ Square 8 mm | | |
| Seal: | ■ Hollow section clamped profile | | |
| Door closing: | ■ left-hand | | |
| Mounting panel: | ■ Stainless steel | ■ Aluminium | |
| Protection class: | ■ IP 66 | ■ IP 69 K | |

Accessory equipment

- Rain roof or weather roof
- Cable flange plate

Customised features

- | | | |
|------------------------|--------------------------------|------------|
| ■ Roof pitch | ■ Roof overhang | ■ Cut-outs |
| ■ Holes | ■ Sheet metal thickness 2-3 mm | |
| ■ Special requirements | | |